

Feature	Emperor Cable Cleat	Vari-cleat Cable Cleat	Vulcan Cable Cleat	Alpha Cable Cleat	ProTect Cable Strap	2-Hole Clamp + Triplex Surround
<b>Material</b>	316L SS	316L SS Strap Cast Aluminum Base	316L SS	Extruded Aluminum	316L SS	Cast Aluminum Clamp LSF Triplex Surround
<b>Integral LSF Liner</b>	Yes	Yes	Yes	No	Yes	Yes
<b>Range Take</b>	Yes	Yes	Yes	Small	Small	Yes
<b>Tensile Strength</b>	High	Medium	Medium	Medium	Medium	Low
<b>Single Cable Cleating</b>	34-72mm Standard Larger Sizes Available	31-215mm	33-153mm	No	N/A	38-135mm
<b>Dual Cable Cleating</b>	Available	No	No	No	No	No
<b>Trefoil Cable Cleating</b>	23-128mm	19-118mm	23-85mm	23.2-74.6mm	23-85mm	28-47mm
<b>Quad Cable Cleating</b>	Available	Available	Yes	No	No	No
<b>Bundled Cable Cleating</b>	No	Max dia = 215mm	Max dia = 153mm	No	No	No
<b>Suitability for Triplex Cable Assemblies</b>	Yes	No	Yes	No	Yes	Yes
<b>EN50368:2003 Certified</b>	Yes	Yes	Yes	Yes	Yes	Yes
<b>Short Circuit Withstand</b>	Consult kVA Strategies	Consult kVA Strategies	Consult kVA Strategies	Consult kVA Strategies	Consult kVA Strategies	Consult kVA Strategies
<b>Underwriters Laboratories (UL®) Short Circuit Report</b>	Yes	No	No	No	No	No
<b>Specials Availability</b>	Yes	No	Yes	No	Yes	No
<b>Ease of Installation</b>	Easy	Moderate	Moderate	Easy	Easy	Easy